



SERIES NAVE
TWO-WAY SWITCH
CODE 239613



Datasheet

Electrical characteristics

Rated current	10A
Supply Voltage	250V~ 50/60Hz
Poles	2P
Rated insulation voltage	-
Insulation Class	-
CAM layout	-
Function Apparatus Control	Two way switches
Type of protection	None

Mechanical characteristics

Manufacturing material	-
Treatment type	-
Surface finishing	-
Color	-
Execution	-
Dimensions	-
Front-plate dimension	-
Hole type	-
IP Protection degree	-
Additional IPdegree protection	-
Shock resistance	IK08 according to IEC/EN 62262
Resistance to Glow wire	-
Flame rating according UL94	-
Corrosivity category	-
Net Weight	0.18 KG
Working Environment Temp.	Min: - ;Max: -
Warehousing Temperature	Min: - ;Max: -

Technical data switch

Thermal current	10 A
Rated short-circuit current	-
Terminals type	Screw - indirect clamping
Conductors section (Cu)	Min: 1 mm ² ;Max: 2.5 mm ²
Terminal tightening torque	1 Nm
Auxiliary status contacts	-
Padlockable handle	-
Operating category	

Reference Standards and Directives

Certification and approval marks

Directives 2014/35/EU (LVD)

Reference Standards

The images are purely indicative. Palazzoli reserves the right to make changes without notice.