
CAM-EX ISOLATOR SWITCH IN ALUMINIUM ALLOY 4X16A IP66/IP67 2D 3G nR

SERIES CAM-Ex SWITCH

CODE 272143EX





Datasheet

Specifications

Net Weight	0.768 KG
Rated current	16A
Frequency	50/60Hz
IP Protection degree	IP66/IP67
Poles	4P
Rated operating voltage	500V~
Manufacturing material	Marine aluminium alloy (EN 44300)
Width	- mm
Execution	Wall mounting
Type of protection	None
Insulation Class	I
Dimensions	140X92X103 mm
Hole type	M25
Number of entries in enclosure	2
CAM layout	3
Function Apparatus Control	One way switches

Reference Standards and Directives

Certification and approval marks	CE, NYCE COLOMBIA, EX, IECEx, TUV EX
Directives	2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/34/EU (ATEX), 2014/35/EU (LVD)
Reference Standards	EN 60079-0/A11:2013, EN 60079-0:2012, EN 60079-15:2010 , EN 60079-31:2014, EN 60947-1:2007, EN 60947-1:2007/A1:2011, EN 60947-3:2009, EN 60947-3:2009/A1:2012, EN IEC 63000:2018

Atex characteristics

ATEX application zone	Zones 2-21-22
Dust Atex execution (Tmax1)	II 2D - Ex tb IIIC T85 °C Db
Gas Atex execution (Tmax1)	II 3G - Ex nR IIC T6 Gc

The images are purely indicative. Palazzoli reserves the right to make changes without notice.

Palazzoli S.p.A. - Società unipersonale - Via F. Palazzoli, 31 - 25128 Brescia - Italy - tel. +39 030 2015.1 - fax +39 030 2015.258 - www.palazzoli.com - export@palazzoli.it