



**SERIES ALUPRES**

**CODE 274401**



## Datasheet

### Electrical characteristics

|                  |   |
|------------------|---|
| Supply Voltage   |   |
| Poles            | - |
| Insulation Class | I |

### Technical data switch

|                         |            |
|-------------------------|------------|
| Conductors section (Cu) | Min: ;Max: |
|-------------------------|------------|

### Mechanical characteristics

|                                |                                             |
|--------------------------------|---------------------------------------------|
| Manufacturing material         | Marine aluminium alloy (EN 44300)           |
| Color                          | Blue RAL 5012 (Cover), Grey RAL 7035 (Base) |
| Execution                      | Wall mounting                               |
| Hole type                      | -                                           |
| IP Protection degree           | -                                           |
| Additional IPdegree protection | -                                           |
| Shock resistance               | IK10 according to IEC/EN 62262              |
| Resistance to Glow wire        | -                                           |
| Flame rating according UL94    | -                                           |
| Corrosivity category           | C4 (ISO 12944)                              |
| Net Weight                     | 5.2 KG                                      |
| Working Environment Temp.      | Min: -40°C ;Max: +90°C                      |
| Warehousing Temperature        | Min: -50°C ;Max: +90°C                      |

### Reference Standards and Directives

|                                  |
|----------------------------------|
| Certification and approval marks |
| Directives                       |
| Reference Standards              |

The images are purely indicative. Palazzoli reserves the right to make changes without notice.