




**SERIES CAM-Ex**

**CODE 282407EX**



### Datasheet

#### Specifications

Net Weight	4.228 KG
Rated current	63A
Frequency	50/60Hz
IP Protection degree	IP65
Poles	4P
Rated operating voltage	400V~
Manufacturing material	Aluminum alloy
Width	185 mm
Execution	Wall mounting
Type of protection	None
Insulation Class	I
Dimensions	225X185X170 mm
Hole type	M32
Number of entries in enclosure	3
CAM layout	7
Function Apparatus Control	Selector switches

#### Reference Standards and Directives

Certification and approval marks TUV EX, EX, CE, NYCE COLOMBIA, IECEx

Directives 2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/34/EU (ATEX), 2014/35/EU (LVD)

Reference Standards EN 60079-0/A11:2013, EN 60079-0:2012, EN 60079-15:2010, EN 60079-31:2014, EN 60947-1:2007, EN 60947-1:2007/A1:2011, EN 60947-3:2009, EN 60947-3:2009/A1:2012, EN IEC 63000:2018

#### Atex characteristics

ATEX application zone	Zones 2-21-22
Dust Atex execution (Tmax1)	II 2D - Ex tb IIIC T85 °C Db
Gas Atex execution (Tmax1)	II 3G - Ex nR IIC T6 Gc

The images are purely indicative. Palazzoli reserves the right to make changes without notice.