




SERIES CAM-Ex
CMP_INT
CODE 292101EX



Datasheet

Specifications

Net Weight	0.763 KG
Rated current	16A
Frequency	50/60Hz
IP Protection degree	IP66
Poles	2P
Rated operating voltage	500V~
Manufacturing material	Palazzoli Thermosetting GRP
Width	92 mm
Execution	Wall mounting
Type of protection	None
Insulation Class	II
Dimensions	175X92X122 mm
Hole type	M25
Number of entries in enclosure	2
CAM layout	1
Function Apparatus Control	One way switches

Reference Standards and Directives

Certification and approval marks NYCE COLOMBIA, EX, TUV EX, CE, IECEx

Directives 2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/34/EU (ATEX), 2014/35/EU (LVD)

Reference Standards EN 60079-0/A11:2013, EN 60079-0:2012, EN 60079-15:2010, EN 60079-31:2014, EN 60947-1:2007, EN 60947-1:2007/A1:2011, EN 60947-3:2009, EN 60947-3:2009/A1:2012, EN IEC 63000:2018

Atex characteristics

ATEX application zone	Zones 2-21-22
Dust Atex execution (Tmax1)	II 2D - Ex tb IIIC T85 °C Db
Gas Atex execution (Tmax1)	II 3G - Ex nR IIC T6 Gc

The images are purely indicative. Palazzoli reserves the right to make changes without notice.