




**SERIES CAM-Ex
SWITCH**
CODE 292203EX



Datasheet

Specifications

| | |
|--------------------------------|-----------------------------|
| Net Weight | 0.788 KG |
| Rated current | 25A |
| Frequency | 50/60Hz |
| IP Protection degree | IP66 |
| Poles | 4P |
| Rated operating voltage | 500V~ |
| Manufacturing material | Palazzoli Thermosetting GRP |
| Width | 92 mm |
| Execution | Wall mounting |
| Type of protection | None |
| Insulation Class | II |
| Dimensions | 175X92X122 mm |
| Hole type | M25 |
| Number of entries in enclosure | 2 |
| CAM layout | 3 |
| Function Apparatus Control | One way switches |

Reference Standards and Directives

Certification and approval marks TUV EX, EX, NYCE COLOMBIA, CE, IECEx

Directives 2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/34/EU (ATEX), 2014/35/EU (LVD)

Reference Standards EN 60079-0/A11:2013, EN 60079-0:2012, EN 60079-15:2010, EN 60079-31:2014, EN 60947-1:2007, EN 60947-1:2007/A1:2011, EN 60947-3:2009, EN 60947-3:2009/A1:2012, EN IEC 63000:2018

Atex characteristics

| | |
|-----------------------------|------------------------------|
| ATEX application zone | Zones 2-21-22 |
| Dust Atex execution (Tmax1) | II 2D - Ex tb IIIC T85 °C Db |
| Gas Atex execution (Tmax1) | II 3G - Ex nR IIC T6/T5 Gc |

The images are purely indicative. Palazzoli reserves the right to make changes without notice.