



**SERIES ULYSSE  
INTERLOCKED SOCKET**  
**CODE 400136**



### Datasheet

#### Electrical characteristics

|                          |                         |
|--------------------------|-------------------------|
| Rated current            | 16A                     |
| Supply Voltage           | 400V 50/60Hz ●          |
| Poles                    | 3P+ $\frac{1}{5}$       |
| Clock Position           | 6h                      |
| Rated insulation voltage | 690 V                   |
| Insulation Class         | II                      |
| Type of protection       | Fuse 10,3x38 gG max 16A |
| Signal plug inserted     | -                       |

#### Mechanical characteristics

|                                |                                |
|--------------------------------|--------------------------------|
| Manufacturing material         | Palazzoli Thermosetting GRP    |
| Treatment type                 | -                              |
| Surface finishing              | -                              |
| Color                          | Grey RAL 7035, Blue RAL 5015   |
| Width                          | 125 mm                         |
| Execution                      | Wall mounting                  |
| Hole type                      | Pg29                           |
| IP Protection degree           | IP66/IP67                      |
| Additional IPdegree protection | -                              |
| Shock resistance               | IK10 according to IEC/EN 62262 |
| Resistance to Glow wire        | 960°C                          |
| Flame rating according UL94    | V-0                            |
| Corrosivity category           | -                              |
| Net Weight                     | 2.513 KG                       |
| Working Environment Temp.      | Min: -50°C ;Max: +60°C         |
| Warehousing Temperature        | Min: -50°C ;Max: +80°C         |

#### Technical data switch

|                             |   |
|-----------------------------|---|
| Thermal current             | 16 A  |
| Rated short-circuit current | 10 kA   |
| Terminals type              | Screw - indirect clamping                       |
| Conductors section (Cu)     | Min: 1 mm <sup>2</sup> ;Max: 10 mm <sup>2</sup> |
| Terminal tightening torque  | 2 Nm  |
| Auxiliary status contacts   | Max 2 (optional)                                |
| Padlockable handle          | 2 locks Ø6 mm max                               |

#### Operating category

| Categoria Rating | Tensione Voltage | Corrente / Potenza Current / Power |
|------------------|------------------|------------------------------------|
| AC-22A           | 230 V            | 16 A                               |
|                  | 400 V            | 16 A                               |
|                  | 500 V            | 16 A                               |
|                  | 690 V            | 16 A                               |
| AC-23A           | 230 V            | 16 A                               |
|                  | 400 V            | 16 A                               |
|                  | 500 V            | 16 A                               |
|                  | 690 V            | 16 A                               |
| AC-23A / AC-3    | 230 V            | 5.1 kW                             |
|                  | 400 V            | 8.9 kW                             |
|                  | 500 V            | 11.1 kW                            |
|                  | 690 V            | 15.3 kW                            |

#### Reference Standards and Directives

Certification and approval marks CE, UKCA

Directives 2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/35/EU (LVD)

Reference Standards EN 60309-1:1999, EN 60309-1:1999/A1:2007, EN 60309-1:1999/A1AC:2014, EN 60309-1:1999/A2:2012, EN 60309-2:1999, EN 60309-2:1999/A1:2007, EN 60309-2:1999/A2:2012, EN 60309-4:2007, EN 60309-4:2007/A1:2012, EN IEC 63000:2018

The images are purely indicative. Palazzoli reserves the right to make changes without notice.