





**SERIES ULYSSE  
INTERLOCKED SOCKET**  
**CODE 403326**



### Datasheet

#### Electrical characteristics

Rated current	63A
Supply Voltage	230V 50/60Hz ●
Poles	2P+ $\frac{1}{2}$
Clock Position	6h
Rated insulation voltage	690 V
Insulation Class	II
Type of protection	Switch MCB 63A curve C
Signal plug inserted	1 contact pilot

#### Technical data switch

Thermal current	63 A
Rated short-circuit current	6 kA
Terminals type	Screw - indirect clamping
Conductors section (Cu)	Min: 6 mm <sup>2</sup> ;Max: 16 mm <sup>2</sup>
Terminal tightening torque	3 Nm
Auxiliary status contacts	Max 2 (combine with MGT)
Padlockable handle	2 locks Ø6 mm max
Operating category	AC-23A / AC-3 63A - 250V

#### Mechanical characteristics

Manufacturing material	Palazzoli Thermosetting GRP
Treatment type	-
Surface finishing	-
Color	Grey RAL 7035, Blue RAL 5015
Width	250 mm
Execution	Wall mounting
Hole type	2xPg29
IP Protection degree	IP66/IP67
Additional IPdegree protection	-
Shock resistance	IK10 according to IEC/EN 62262
Resistance to Glow wire	960°C
Flame rating according UL94	V-0
Corrosivity category	-
Net Weight	5.5 KG
Working Environment Temp.	Min: -25°C ;Max: +50°C
Warehousing Temperature	Min: -50°C ;Max: +80°C

#### Reference Standards and Directives

Certification and approval marks	CE, UKCA
Directives	2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/30/EU (EMC), 2014/35/EU (LVD)
Reference Standards	EN 60309-1:1999, EN 60309-1:1999/A1:2007, EN 60309-1:1999/A1AC:2014, EN 60309-1:1999/A2:2012, EN 60309-2:1999, EN 60309-2:1999/A1:2007, EN 60309-2:1999/A2:2012, EN 60309-4:2007, EN 60309-4:2007/A1:2012, EN 60947-2/A1:2020, EN 60947-2:2017, EN IEC 63000:2018

The images are purely indicative. Palazzoli reserves the right to make changes without notice.