




SERIES ULYSSE
SOCKET OUTLET
CODE 409873



Datasheet

Electrical characteristics

Rated current	16A
Supply Voltage	230/24V~ 50/60Hz
Poles	2P
Clock Position	-
Rated insulation voltage	690 V
Insulation Class	II
Type of protection	-
Signal plug inserted	-

Technical data switch

Thermal current	6,25 A
Rated short-circuit current	-
Terminals type	Screw - indirect clamping
Conductors section (Cu)	Min: ;Max:
Terminal tightening torque	0,6 Nm
Auxiliary status contacts	-
Padlockable handle	-
Operating category	-

Mechanical characteristics

Manufacturing material	Palazzoli Thermosetting GRP
Treatment type	-
Surface finishing	-
Color	Grey RAL 7035, Blue RAL 5015
Width	125 mm
Execution	Wall mounting
Hole type	Pg29
IP Protection degree	IP66/IP67
Additional IPdegree protection	-
Shock resistance	IK10 according to IEC/EN 62262
Resistance to Glow wire	960°C
Flame rating according UL94	V-0
Corrosivity category	-
Net Weight	3.3 KG
Working Environment Temp.	Min: -25°C ;Max: +50°C
Warehousing Temperature	Min: -50°C ;Max: +80°C

Reference Standards and Directives

Certification and approval marks	UKCA, CE
Directives	2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/35/EU (LVD)
Reference Standards	EN 60309-1:1999, EN 60309-1:1999/A1:2007, EN 60309-1:1999/A1AC:2014, EN 60309-1:1999/A2:2012, EN 60309-2:1999, EN 60309-2:1999/A1:2007, EN 60309-2:1999/A2:2012, EN 61558-1/A1:2009, EN 61558-1/AC:2006, EN 61558-1:2005, EN 61558-2-6:2009, EN IEC 63000:2018

The images are purely indicative. Palazzoli reserves the right to make changes without notice.