
TAIS MIGNON SOCKET 2P+E 10/16A 250V PANEL MOUNTING

SERIES TAIS-MIGNON SOCKET OUTLET

CODE 431252





Datasheet

Electrical characteristics

Rated current	16A
Supply Voltage	250V~ 50/60Hz
Poles	2P+ ⏚
Clock Position	-
Rated insulation voltage	-
Signal plug inserted	-

Reference Standards and Directives

Certification and approval marks	CB IMQ, CE, IMQ
Directives	2011/65/EU (RoHS), 2012/19/EU (WEEE), Reg. EU 2023/988 (GPSR)
Reference Standards	CEI 23-50/V1:2008, CEI 23-50/V2:2011, CEI 23-50/V3:2015, CEI 23-50/V4:2015, CEI 23 -50:2007, EN IEC 63000:2018, IEC 60884 -1:2022

Mechanical characteristics

Manufacturing material	Technopolymer Recyclable Palazzoli
Alveolus/plugs treatment	-
Color	Blue RAL 5015
Tightening diameter	-
Execution	Panel mounting
IP Protection degree	IP44
Additional IPdegree protection	-
Shock resistance	IK04 according to IEC/EN 62262
Resistance to Glow wire	960°C
Flame rating according UL94	V-0
Terminals type	Screw - direct tightening
Conductors section (Cu)	Min: 1.5 mm^2 ;Max: 2.5 mm^2
Terminal tightening torque	0,8 Nm
Net Weight	0.14 KG
Working Environment Temp.	Min: -25°C ;Max: +70°C
Warehousing Temperature	Min: -50°C ;Max: +80°C

The images are purely indicative. Palazzoli reserves the right to make changes without notice.

Palazzoli S.p.A. - Società unipersonale - Via F. Palazzoli, 31 - 25128 Brescia - Italy - tel. +39 030 2015.1 - fax +39 030 2015.258 - www.palazzoli.com - export@palazzoli.it