# ENERGY TAIS ASSEMBLY ACS ON SUPPORT WITH 7 SWITCHED INTERLOCKED SOCKETS 2X 16A 2P+E 230V/2X 16A 3P+E 400V/2X 32A 3P+N+E 400V/1X63A 3P+N+E 230-400V TRANSFORMER 2P 16A 2P 230-400V 230-400V IP65

**SERIES ENERGY TAIS**
**DISTRIBUTION BOARD CONSTR.SITI**

**CODE 500830**



## Datasheet

### Specifications

| | |
|---|---|
| Net Weight | 170 KG |
| | ASC3 |
| power | 100 kW |
| Storage room temperature MIN | -50°C |
| Max. Amb. Temp. | +50°C |
| Min. Amb. Temp. | -25°C |
| Shock resistance | IK10 according to IEC/EN 62262 |
| Storage room temperature MAX | +80°C |
| Rated current | 200A |
| Frequency | 50/60Hz |
| IP Protection degree | IP65 |
| Poles | 4P |
| Rated operating voltage | 230-400V~ |
| Manufacturing material | Palazzoli Thermosetting GRP |
| Socket Protection | With magnetothermic |
| Execution | Support |
| Outlet Sockets | 9 |
| Outfit | WITH SUPPORT |
| Insulation Class | II |
| Dimensions | 1853X1685X748 mm |
| Hole type | M63 |
| Transf. sock.-outl. 16A 2P 24V | 2 |
| Interlocked sock.-outl. 16A 3P | 2 |
| Interlocked sock.-outl. 32A 3P | 2 |
| Interlocked sock.-outl. 63A 3P | 1 |
| Interl. sock. 16A 2P+E 230V | 2 |
| Switch type | SEZ 4P 200A + 3xMCB 4P 63A |
| Differential protection | 3 x 63A 4P 30mA |
| Emergency button | Yes |

### Reference Standards and Directives

| | |
|---|---|
| Certification and approval marks | UKCA, CE |
| Directives | 2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/30/EU (EMC), 2014/35/EU (LVD) |
| Reference Standards | EN 61439-1:2011, EN 61439-4:2013, EN IEC 63000:2018 |

The images are purely indicative. Palazzoli reserves the right to make changes without notice.

Palazzoli S.p.A. - Società unipersonale - Via F. Palazzoli, 31 - 25128 Brescia - Italy - tel. +39 030 2015.1 - fax +39 030 2015.258 - www.palazzoli.com - export@palazzoli.it