

SERIES ENERGY TAIS
DISTRIBUTION BOARD CONSTR.SITI
CODE 500833



Datasheet

Specifications

| | |
|--------------------------------|--------------------------------|
| Net Weight | 161 KG |
| | ASC3 |
| power | 100 kW |
| Storage room temperature MIN | -50°C |
| Max. Amb. Temp. | +50°C |
| Min. Amb. Temp. | -25°C |
| Shock resistance | IK10 according to IEC/EN 62262 |
| Storage room temperature MAX | +80°C |
| Rated current | 200A |
| Frequency | 50/60Hz |
| IP Protection degree | IP65 |
| Poles | 4P |
| Rated operating voltage | 230-400V~ |
| Manufacturing material | Palazzoli Thermosetting GRP |
| Socket Protection | With magnetothermic |
| Execution | Support |
| Outlet Sockets | 9 |
| Outfit | WITH SUPPORT |
| Insulation Class | II |
| Dimensions | 1853X1685X748 mm |
| Hole type | M63 |
| Interlocked sock.-outl. 16A 3P | 3 |
| Interlocked sock.-outl. 32A 3P | 2 |
| Interlocked sock.-outl. 63A 3P | 1 |
| Interl. sock. 16A 2P+E 230V | 3 |
| Switch type | SEZ 4P 200A + 3xMCB 4P 63A |
| Differential protection | 3 x 63A 4P 30mA |

Reference Standards and Directives

Certification and approval marks CE, UKCA

Directives 2011/65/EU (RoHS), 2012/19/EU (WEEE),
2014/30/EU (EMC), 2014/35/EU (LVD)

Reference Standards EN 61439-1:2011, EN 61439-4:2013, EN IEC
63000:2018

The images are purely indicative. Palazzoli reserves the right to make changes without notice.