





**SERIES ENERGY BOX
DISTRIBUTION BOARD
CONSTR. SITE
CODE 501530**



Datasheet

Electrical characteristics

Insulation Class	I
Rated insulation voltage	500 V
Dissipable Power	-

Reference Standards and Directives

Certification and approval marks	UKCA, CE, NYCE COLOMBIA
Directives	2014/35/EU (LVD)

Mechanical characteristics

Manufacturing material	Technopolymer Recyclable Palazzoli
Color	Blue RAL 5015
Execution	Portable
Door type	-
Number and type of closures	2 triangle key closure
N. of modules on DIN rail	-
Internal working depth	190
IP Protection degree	-
Shock resistance	IK10 according to IEC/EN 62262
Resistance to Glow wire	960°C
Flame rating according UL94	V-0
Corrosivity category	-
Working Environment Temp.	Min: -25 °C ;Max: +50 °C
Warehousing Temperature	Min: -30 °C ;Max: +70 °C
Dimensions	680X585X340 mm
Internal dimensions	-
Net Weight	10.7 KG
Maximum permissible load	Mounting surfaces: 20 kg; On the doors: 0 kg; On the bottom: 20 kg

Reference Standards	EN 62208:2011
---------------------	---------------

The images are purely indicative. Palazzoli reserves the right to make changes without notice.