




**SERIES CONTACT
TERMINAL BLOCK
CODE 532725**



Codici	A (mm)	B (mm)	C (mm)	testo della vite che sporge dalla morsettiera (mm)
532725	70	4,75	19,5	-
532735	70	4,75	24,5	-
532745	93	4,75 x 7 (foro obliquo)	24,5	-
532743	100	4,75	25,2	28,2
532748	175	4,75	25,5	-
532755	70	4,75	22,5	-
532765	93	4,75 x 7 (foro obliquo)	24,5	-
532768	175	4,75	30	-



Datasheet

Specifications

Connecting Terminals	Double side-by-side terminals
Manufacturing material	Ceramic
Contact material	Brass
Terminals type	Screw - direct tightening
No. poles for section	4x6 mm ²
Conductors section (Cu)	Min: 1.5 ;Max: 6 mm ²
Terminal tightening torque	0,8 Nm
Rated current	41A
Rated operating voltage	450V ●
Rated impul. withstand voltage	6,000
Functional maintenance	-
Working Environment Temp.	Min: -50°C ;Max: +300°C
Warehousing Temperature	Min: -50°C ;Max: +100°C
Net Weight	0.07 KG

Reference Standards and Directives

Directives	2011/65/EU (RoHS)2012/19/EU (WEEE)2014/35/EU (LVD)
Reference Standards	EN 60999-1:2000EN IEC 63000:2018

The images are purely indicative. Palazzoli reserves the right to make changes without notice.