




**SERIES TAIS CUBE
EMPTY DISTRIBUTION BOARD**
CODE 550003



| MISURA | A | B | C |
|--------|-----|------|-----|
| 1 | 258 | 304 | 160 |
| 2 | 340 | 430 | 180 |
| 3 | 449 | 506 | 220 |
| 4 | 449 | 656 | 220 |
| 5 | 558 | 656 | 260 |
| 6 | 631 | 807 | 300 |
| 7 | 848 | 1058 | 350 |



Datasheet

Electrical characteristics

| | |
|--------------------------|---------------------|
| Insulation Class | II |
| Rated insulation voltage | 1000 Vac - 1500 Vdc |
| Dissipable Power | 138W |

Reference Standards and Directives

Certification and approval marks UKCA, NYCE COLOMBIA, CE

Directives 2014/35/EU (LVD)

Reference Standards EN 62208:2011

Mechanical characteristics

| | |
|-----------------------------|---|
| Manufacturing material | Palazzoli Thermosetting GRP |
| Color | Grey RAL 7035 |
| Execution | Wall mounting |
| Door type | BLIND |
| Number and type of closures | 2 triangle key closure |
| N. of modules on DIN rail | - |
| Internal working depth | 160 |
| IP Protection degree | IP66 |
| Shock resistance | IK10 according to IEC/EN 62262 |
| Resistance to Glow wire | 960°C |
| Flame rating according UL94 | V-0 |
| Corrosivity category | - |
| Working Environment Temp. | Min: -30 °C ;Max: +90 °C |
| Warehousing Temperature | Min: -50 °C ;Max: +90 °C |
| Dimensions | 449X506X220 mm (WHD) |
| Internal dimensions | 390X450X160 mm |
| Net Weight | 6.782 KG |
| Maximum permissible load | On the doors: 10 kg, On the bottom: 30 kg, Mounting surfaces: 30 kg |

The images are purely indicative. Palazzoli reserves the right to make changes without notice.