
TAIS CUBE DISTRIBUTION BOARD IN THERMOSETTING GRP WITH TRANSPARENT DOOR 340X430X180 SIZE 2 IP66

SERIES TAIS CUBE
EMPTY DISTRIBUTION BOARD

CODE 550032





MISURA	A	B	C
1	258	304	160
2	340	430	180
3	449	506	220
4	449	656	220
5	558	656	260
6	631	807	300
7	848	1058	350

Datasheet

Electrical characteristics

Insulation Class	II
Rated insulation voltage	1000 Vac - 1500 Vdc
Dissipable Power	12,5W

Reference Standards and Directives

Certification and approval marks	IMQ, UKCA, NYCE COLOMBIA, CE
Directives	2014/35/EU (LVD)
Reference Standards	EN 62208:2011

Mechanical characteristics

Manufacturing material	Palazzoli Thermosetting GRP
Color	Grey RAL 7035
Execution	Wall mounting
Door type	TRANSPARENT
Number and type of closures	2 triangle key closure
N. of modules on DIN rail	36 (12X3)
Internal working depth	120
IP Protection degree	IP66
Shock resistance	IK09 according to IEC/EN 62262
Resistance to Glow wire	960°C (Box), 650°C (Window)
Flame rating according UL94	V-0
Corrosivity category	-
Working Environment Temp.	Min: -30 °C ;Max: +60 °C
Warehousing Temperature	Min: -50 °C ;Max: +70 °C
Dimensions	340X430X180 mm
Internal dimensions	280X375X120 mm
Net Weight	4.41 KG
Maximum permissible load	On a base plate: 20 kg; Total: 40 kg; On the doors: 0 kg; Mounting supports: 20 kg

The images are purely indicative. Palazzoli reserves the right to make changes without notice.

Palazzoli S.p.A. - Società unipersonale - Via F. Palazzoli, 31 - 25128 Brescia - Italy - tel. +39 030 2015.1 - fax +39 030 2015.258 - www.palazzoli.com - export@palazzoli.it