



**SERIES TAIS-MIGNON  
ENCLOSURE**

**CODE 559022**



### Datasheet

#### Electrical characteristics

Insulation Class	II
Rated insulation voltage	-
Rated operating voltage	-
Dissipable Power	2,8W

#### Mechanical characteristics

Manufacturing material	Palazzoli Thermosetting GRP
Treatment type	-
Surface finishing	-
Color	Blue RAL 5015 (Cover), Grey RAL 7035 (Base)
Execution	Wall mounting
Height Box	28 mm
Cover height	23 mm
Cover type	With transparent door
N. of modules on DIN rail	-
Hole type	M20
Window type	
IP Protection degree	IP44
Additional IPdegree protection	-
Shock resistance	IK04 according to IEC/EN 62262
Resistance to Glow wire	960°C
Flame rating according UL94	V-0
Corrosivity category	-
Working Environment Temp.	Min: -25°C ;Max: +70°C
Warehousing Temperature	Min: -50°C ;Max: +80°C
Dimensions	62X80X62 mm
Internal dimensions	-
Net Weight	0.17 KG

#### Reference Standards and Directives

Certification and approval marks CE, -, UKCA

Directives 2014/35/EU (LVD)

Reference Standards EN 60670-1:2005, EN 60670-1:2005/A1:2013, EN 60670-1:2005/AC:2007, EN 60670-1:2005/AC:2010

The images are purely indicative. Palazzoli reserves the right to make changes without notice.