TAIS MIGNON WALL MOUNTING ENCLOSURE FOR PANEL DEVICES TICINO MAGIC 2 INLETS 3/8"

SERIES TAIS-MIGNON ENCLOSURE

CODE 559031



Datasheet

Electrical characteristics

Insulation Class	II
Rated insulation voltage	-
Rated operating voltage	-
Dissipable Power	2,8W

Mechanical characteristics

Manufacturing material	Palazzoli Thermosetting GRP
Treatment type	-
Surface finishing	-
Color	Grey RAL 7035 (Base), Blue RAL 5015 (Cover)
Execution	Wall mounting
Height Box	28 mm
Cover height	23 mm
Cover type	With transparent door
N. of modules on DIN rail	-
Hole type	M16 (5 - 10 mm)
Window type	
IP Protection degree	IP44
Additional IPdegree protection	-
Shock resistance	IK04 according to IEC/EN 62262
Resistance to Glow wire	960°C
Flame rating according UL94	V-0
Corrosivity category	-
Working Environment Temp.	Min: -25°C ;Max: +70°C
Warehousing Temperature	Min: -50°C ;Max: +80°C
Dimensions	62X80X62 mm
Internal dimensions	-
Net Weight	0.16 KG

Reference Standards and Directives

Certification and approval marks	CE, UKCA, -
Directives	2014/35/EU (LVD)
Reference Standards	EN 60670-1:2005, EN 60670-1:2005/A1:2013, EN 60670-1:2005/AC:2007, EN 60670 -1:2005/AC:2010

The images are purely indicative. Palazzoli reserves the right to make changes without notice.

Palazzoli S.p.A. - Società unipersonale - Via F. Palazzoli, 31 - 25128 Brescia - Italy - tel. +39 030 2015.1 - fax +39 030 2015.258 - www.palazzoli.com - export@palazzoli.it