# UNI-EX PLASTIC CABLE GLAND WITH LONG THREAD PG9 EX CAT. 2D 2G

**SERIES UNI-Ex**
**CABLE GLAND**
**CODE 571109EX**



## Datasheet

### Specifications

| | |
|---|---|
| Net Weight | 0.01 KG |
| IP Protection degree | IP68 |
| Max assembly hole | 16 mm |
| Screw length | 15 mm |
| Pg | 9 |
| Tightening diameter | 3,5 - 8,5 mm |

### Reference Standards and Directives

| | |
|---|---|
| Certification and approval marks | CE, EX |
| Directives | 2014/34/EU (ATEX) |
| Reference Standards | EN 60079-31:2014, EN 60079-7:2015, EN 60079-7:2015/A1:2018, EN IEC 60079-0:2018 |

### Atex characteristics

| | |
|---|---|
| ATEX application zone | Zones 1-2-21-22 |
| Dust Atex execution (Tmax1) | II 2D - Ex tb IIIC Db |
| Gas Atex execution (Tmax1) | II 2G - Ex eb IIC Gb |

The images are purely indicative. Palazzoli reserves the right to make changes without notice.

Palazzoli S.p.A. - Società unipersonale - Via F. Palazzoli, 31 - 25128 Brescia - Italy - tel. +39 030 2015.1 - fax +39 030 2015.258 - www.palazzoli.com - export@palazzoli.it