



**SERIES TOP-TER  
SOCKET OUTLET  
CODE 579840**



## Datasheet

### Electrical characteristics

Rated current	10/16A
Supply Voltage	250V~ 50/60Hz
Poles	2P+ $\perp$
Clock Position	-
Rated insulation voltage	-
Signal plug inserted	-

### Reference Standards and Directives

Certification and approval marks	CE
Directives	2011/65/EU (RoHS), 2012/19/EU (WEEE), Reg. EU 2023/988 (GPSR)
Reference Standards	CEI 23-50/V1:2008, CEI 23-50/V2:2011, CEI 23-50/V3:2015, CEI 23-50/V4:2015, CEI 23 -50:2007, EN IEC 63000:2018, IEC 60884 -1/A1:2006, IEC 60884-1/A2:2013, IEC 60884 -1:2002

### Mechanical characteristics

Manufacturing material	Technopolymer Recyclable Palazzoli
Alveolus/plugs treatment	-
Color	Grey RAL 7035
Tightening diameter	-
Execution	Panel mounting
IP Protection degree	IP66
Additional IPdegree protection	-
Shock resistance	IK08 according to IEC/EN 62262
Resistance to Glow wire	650°C (Box), 850°C (Socket)
Flame rating according UL94	V-2 (Socket), HB (Box)
Terminals type	Screw - indirect clamping
Conductors section (Cu)	Min: 1 mm <sup>2</sup> ;Max: 2.5 mm <sup>2</sup>
Terminal tightening torque	0,8 Nm
Net Weight	0.08 KG
Working Environment Temp.	Min: -25°C ;Max: +50°C
Warehousing Temperature	Min: -30°C ;Max: +70°C

The images are purely indicative. Palazzoli reserves the right to make changes without notice.