





**SERIES ENERGY BOX  
EMPTY DISTRIBUTION BOARD**

**CODE 601663**



## Datasheet

### Electrical characteristics

|                          |       |
|--------------------------|-------|
| Insulation Class         | I     |
| Rated insulation voltage | 500 V |
| Dissipable Power         | -     |

### Reference Standards and Directives

|                                  |                  |
|----------------------------------|------------------|
| Certification and approval marks | UKCA, CE         |
| Directives                       | 2014/35/EU (LVD) |

### Mechanical characteristics

|                             |                                                                    |
|-----------------------------|--------------------------------------------------------------------|
| Manufacturing material      | Technopolymer Recyclable Palazzoli                                 |
| Color                       | Blue RAL 5015                                                      |
| Execution                   | Portable                                                           |
| Door type                   | -                                                                  |
| Number and type of closures | 2 triangle key closure                                             |
| N. of modules on DIN rail   | 12+5+12                                                            |
| IP Protection degree        | IP65                                                               |
| Shock resistance            | IK10 according to IEC/EN 62262                                     |
| Resistance to Glow wire     | 960°C                                                              |
| Flame rating according UL94 | V-0                                                                |
| Corrosivity category        | -                                                                  |
| Working Environment Temp.   | Min: -25 °C ;Max: +50 °C                                           |
| Warehousing Temperature     | Min: -30 °C ;Max: +70 °C                                           |
| Dimensions                  | 680X585X340 mm                                                     |
| Internal dimensions         | -                                                                  |
| Net Weight                  | 14.35 KG                                                           |
| Maximum permissible load    | Mounting surfaces: 20 kg; On the bottom: 20 kg; On the doors: 0 kg |

|                     |               |
|---------------------|---------------|
| Reference Standards | EN 62208:2011 |
|---------------------|---------------|

The images are purely indicative. Palazzoli reserves the right to make changes without notice.