

**SERIES ENERGY BOX
DISTRIBUTION BOARD CONSTR.SITI
CODE 616007**



Datasheet

Specifications

Net Weight	23 KG
	EBOX
power	40 kW
Storage room temperature MIN	-30°C
Max. Amb. Temp.	+50°C
Min. Amb. Temp.	-25°C
Resistance Glow Wire	650°C (Casing)
Shock resistance	IK10 according to IEC/EN 62262
Storage room temperature MAX	+70°C
Rated current	63A
Frequency	50/60Hz
IP Protection degree	IP65
Poles	4P
Rated operating voltage	400V ●
Manufacturing material	Technopolymer Recyclable Palazzoli
Socket Protection	With magnetothermic
Execution	Portable
Outfit	WITH INSULATING CABINET
Insulation Class	II
Dimensions	680X585X340 mm
Interlocked sock.-outl. 16A 3P	2
Interlocked sock.-outl. 32A 3P	2
Interl. sock. 16A 2P+E 230V	2
Plug type	3P+N+T - 63A
Switch type	MCB 4P - 63A
Differential protection	63A 4P 30mA

Reference Standards and Directives

Certification and approval marks	UKCA, CE
Directives	2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/30/EU (EMC), 2014/35/EU (LVD)
Reference Standards	EN 61439-1:2011, EN 61439-4:2013, EN IEC 63000:2018

The images are purely indicative. Palazzoli reserves the right to make changes without notice.