

SERIES ENERGY BOX
DISTRIBUTION BOARD CONSTR.SITI
CODE 616107



Datasheet

Specifications

| | |
|--------------------------------|---------------------------------------|
| Net Weight | 22 KG |
| | EBOX |
| power | 40 kW |
| Storage room temperature MIN | -30°C |
| Max. Amb. Temp. | +50°C |
| Min. Amb. Temp. | -25°C |
| Resistance Glow Wire | 650°C (Casing) |
| Shock resistance | IK10 according to IEC/EN 62262 |
| Storage room temperature MAX | +70°C |
| Rated current | 63A |
| Frequency | 50/60Hz |
| IP Protection degree | IP65 |
| Poles | 4P |
| Rated operating voltage | 400V ● |
| Manufacturing material | Technopolymer Recyclable Palazzoli |
| Socket Protection | With magnetothermic |
| Execution | Portable |
| Outfit | WITH INSULATING CABINET |
| Insulation Class | II |
| Dimensions | 680X585X340 mm |
| Hole type | M40 |
| Interlocked sock.-outl. 32A 3P | 2 |
| Interl. sock. 16A 2P+E 230V | 2 |
| Interlocked sock.-outl. 16A 3P | 2 |
| Switch type | MCB 4P - 63A |
| Differential protection | 63A 4P 30mA |

Reference Standards and Directives

Certification and approval marks CE, UKCA

Directives 2011/65/EU (RoHS), 2012/19/EU (WEEE),
2014/30/EU (EMC), 2014/35/EU (LVD)

Reference Standards EN 61439-1:2011, EN 61439-4:2013, EN IEC
63000:2018

The images are purely indicative. Palazzoli reserves the right to make changes without notice.