



**SERIES domoTER
REVERSING SWITCH**
CODE 630031



Datasheet

Electrical characteristics

Rated current	16A
Supply Voltage	250V 50/60Hz
Poles	1P
Rated insulation voltage	-
Insulation Class	II
CAM layout	-
Function Apparatus Control	Reversing switches
Type of protection	-

Mechanical characteristics

Manufacturing material	High resistance technopolymer
Treatment type	-
Surface finishing	-
Color	-
Execution	-
Dimensions	-
Depth	-
Front-plate dimension	-
Hole type	-
IP Protection degree	-
Additional IPdegree protection	-
Resistance to Glow wire	-
Flame rating according UL94	-
Corrosivity category	-
Net Weight	0.03 KG
Working Environment Temp.	Min: - ;Max: -
Warehousing Temperature	Min: - ;Max: -

Technical data switch

Thermal current	-
Rated short-circuit current	-
Terminals type	-
Conductors section (Cu)	Min: ;Max:
Terminal tightening torque	-
Auxiliary status contacts	-
Padlockable handle	-
Operating category	-

Reference Standards and Directives

Certification and approval marks	CE, UKCA
Directives	2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/35/EU (LVD)
Reference Standards	EN 60669-1/IS1:2009, EN 60669-1:1999, EN 60669-1:1999/A1:2002, EN 60669-1:1999/A2:2008, EN IEC 63000:2018

The images are purely indicative. Palazzoli reserves the right to make changes without notice.