



SERIES domoTER
SOCKET OUTLET
CODE 630054



Datasheet

Electrical characteristics

Rated current	10/16A
Supply Voltage	250V~
Poles	2P+ \perp
Clock Position	-
Rated insulation voltage	-
Signal plug inserted	-

Reference Standards and Directives

Certification and approval marks	CE
Directives	2011/65/EU (RoHS), 2012/19/EU (WEEE), Reg. EU 2023/988 (GPSR)
Reference Standards	CEI 23-50/V1:2008, CEI 23-50/V2:2011, CEI 23-50/V3:2015, CEI 23-50/V4:2015, CEI 23-50:2007, EN IEC 63000:2018, IEC 60884 -1/A1:2006, IEC 60884-1/A2:2013, IEC 60884 -1:2002

Mechanical characteristics

Manufacturing material	Technopolymer Recyclable Palazzoli
Alveolus/plugs treatment	-
Color	Grey RAL 7035
Tightening diameter	-
Execution	Panel mounting
IP Protection degree	IP20
Additional IPdegree protection	-
Resistance to Glow wire	650°C (Casing), 850°C (Live contact)
Flame rating according UL94	HB (Casing), V-2 (Live contact)
Terminals type	Screw - indirect clamping
Conductors section (Cu)	Min: ;Max:
Terminal tightening torque	0,8 Nm
Net Weight	0.04 KG
Working Environment Temp.	Min: -15°C ;Max: +50°C
Warehousing Temperature	Min: -30°C ;Max: +70°C

The images are purely indicative. Palazzoli reserves the right to make changes without notice.