



SERIES domoTER
SOCKET OUTLET
CODE 630055



Datasheet

Electrical characteristics

| | |
|--------------------------|-------------|
| Rated current | 16A |
| Supply Voltage | 250V~ |
| Poles | 2P+ \perp |
| Clock Position | - |
| Rated insulation voltage | - |
| Signal plug inserted | - |

Reference Standards and Directives

| | |
|----------------------------------|---|
| Certification and approval marks | CE |
| Directives | 2011/65/EU (RoHS), 2012/19/EU (WEEE), Reg. EU 2023/988 (GPSR) |
| Reference Standards | EN IEC 63000:2018, IEC 60884-1/A1:2006, IEC 60884-1/A2:2013, IEC 60884-1:2002, NF C61-314 |

Mechanical characteristics

| | |
|--------------------------------|--------------------------------------|
| Manufacturing material | Technopolymer Recyclable Palazzoli |
| Alveolus/plugs treatment | - |
| Color | Grey RAL 7035 |
| Tightening diameter | - |
| Execution | Panel mounting |
| IP Protection degree | IP20 |
| Additional IPdegree protection | - |
| Resistance to Glow wire | 650°C (Casing), 850°C (Live contact) |
| Flame rating according UL94 | V-2 (Live contact), HB (Casing) |
| Terminals type | Screw - indirect clamping |
| Conductors section (Cu) | Min: ;Max: |
| Terminal tightening torque | 0,8 Nm |
| Net Weight | 0.04 KG |
| Working Environment Temp. | Min: -15°C ;Max: +50°C |
| Warehousing Temperature | Min: -30°C ;Max: +70°C |

The images are purely indicative. Palazzoli reserves the right to make changes without notice.