



**SERIES PT60**  
**SOCKET OUTLET**  
**CODE 641216**



## Datasheet

### Electrical characteristics

Rated current	16A
Supply Voltage	250V~
Poles	2P+ $\frac{1}{2}$
Clock Position	-
Rated insulation voltage	-
Signal plug inserted	-

### Reference Standards and Directives

Certification and approval marks	CE
Directives	2011/65/EU (RoHS), 2012/19/EU (WEEE), Reg. EU 2023/988 (GPSR)
Reference Standards	CEI 23-50/V1:2008, CEI 23-50/V2:2011, CEI 23-50/V3:2015, CEI 23-50/V4:2015, CEI 23- 50:2007, EN IEC 63000:2018, IEC 60884 -1/A1:2006, IEC 60884-1/A2:2013, IEC 60884 -1:2002

### Mechanical characteristics

Manufacturing material	Technopolymer Recyclable Palazzoli
Alveolus/plugs treatment	-
Color	-
Tightening diameter	-
Execution	Panel mounting
IP Protection degree	IP20
Additional IPdegree protection	-
Shock resistance	-
Resistance to Glow wire	-
Flame rating according UL94	-
Terminals type	None
Conductors section (Cu)	Min: ;Max:
Terminal tightening torque	0,8 Nm
Net Weight	0.029 KG
Working Environment Temp.	Min: - ;Max: -
Warehousing Temperature	Min: - ;Max: -

The images are purely indicative. Palazzoli reserves the right to make changes without notice.