

SERIES JANUS
DISTRIBUTION BOARD CONSTR.SITI
CODE 644106



Datasheet

Specifications

Net Weight	9.5 KG
	ASC4
power	18 kW
Storage room temperature MIN	-30°C
Max. Amb. Temp.	+40°C
Min. Amb. Temp.	-20°C
Resistance Glow Wire	650°C (Casing)
Shock resistance	IK08 according to IEC/EN 62262
Storage room temperature MAX	+70°C
Rated current	32A
Frequency	50/60Hz
IP Protection degree	IP65
Poles	4P
Rated operating voltage	400V ●
Manufacturing material	Technopolymer Recyclable Palazzoli
Terminal type	MORSETTIERA 3P 10MMQ C /LAMELL
Socket Protection	With fuses
Execution	Portable
Outfit	WITHOUT PLATE
Insulation Class	II
Dimensions	329X572X325 mm
Interlocked sock.-outl. 16A 3P	1
Interlocked sock.-outl. 32A 3P	1
Interl. sock. 16A 2P+E 230V	2
Switch type	MCB 4P - 32A

Reference Standards and Directives

Certification and approval marks UKCA, CE

Directives 2011/65/EU (RoHS), 2012/19/EU (WEEE),
2014/30/EU (EMC), 2014/35/EU (LVD)

Reference Standards EN 61439-1:2011, EN 61439-4:2013, EN IEC
63000:2018

The images are purely indicative. Palazzoli reserves the right to make changes without notice.