

SERIES ENERGY GO
DISTRIBUTION BOARD CONSTR.SITI
CODE 670033



Datasheet

Specifications

Net Weight	2.5 KG
	ASC1
Shock resistance	IK08 according to IEC/EN 62262
Storage room temperature MIN	-30°C
Max. Amb. Temp.	+50°C
Min. Amb. Temp.	-25°C
UL94 Flamability	V-2 (Live contacts holder)
Resistance Glow Wire	850°C (Live contacts holder) , 650°C (Body of the socket)
Storage room temperature MAX	+70°C
Rated current	16A
Frequency	50/60Hz
IP Protection degree	IP66
Poles	2P
Rated operating voltage	230V
Manufacturing material	Technopolymer Recyclable Palazzoli
Socket Protection	MAGNETOTERMICO E DIFFERENZIALE
Execution	Portable
Outfit	WITHOUT PLATE
Insulation Class	II
Dimensions	122X452X148 mm
Industr. sock.-out. 16A 2P+E 2	2
Plug type	2P+T - 16A
Domestic sock.-outl. 2P+E10/16	1

Reference Standards and Directives

Certification and approval marks	UKCA, CE
Directives	2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/30/EU (EMC), 2014/35/EU (LVD)
Reference Standards	EN 61439-1:2011, EN 61439-4:2013, EN IEC 63000:2018

The images are purely indicative. Palazzoli reserves the right to make changes without notice.