

SERIES ENERGY
DISTRIBUTION METALBOX CONSTR.SITI
CODE 678002



Datasheet

Specifications

Net Weight	90 KG
	EBOX
power	100 kW
Storage room temperature MIN	-30°C
Max. Amb. Temp.	+50°C
Min. Amb. Temp.	-25°C
Shock resistance	IK10 according to IEC/EN 62262
Storage room temperature MAX	+70°C
Rated current	200A
Frequency	50-60Hz
IP Protection degree	IP65
Manufacturing material	High resistance technopolymer
Socket Protection	With magnetothermic
Execution	Wall mounting or on support
Outlet Sockets	8
Outfit	WITH METAL CABINET
Dimensions	1530X740X430
Hole type	M63
Interlocked sock.-outl. 16A 3P	2
Interlocked sock.-outl. 32A 3P	2
Interlocked sock.-outl. 63A 3P	1
Interlocked sock.-outl. 63A 3P	1
Interl. sock. 16A 2P+E 230V	2
Switch type	MCB 4P - 200A
No. of power outgoing	8
Differential protection	63A 4P 30mA
Emergency button	Yes

Reference Standards and Directives

Certification and approval marks UKCA, CE

Directives 2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/30/EU (EMC), 2014/35/EU (LVD)

Reference Standards EN 61439-1:2011, EN 61439-4:2013, EN IEC 63000:2018

The images are purely indicative. Palazzoli reserves the right to make changes without notice.