

SERIES ENERGY
DISTRIBUTION METALBOX RD CONSTR.SITI
CODE 688001



Datasheet

Specifications

Net Weight	90 KG
Storage room temperature MAX	+70°C
Storage room temperature MIN	-30°C
Max. Amb. Temp.	+50°C
Min. Amb. Temp.	-25°C
Shock resistance	IK10 according to IEC/EN 62262
power	100 kW
Rated current	200A
Frequency	50/60Hz
IP Protection degree	IP65
Poles	4P
Rated operating voltage	400V ●
Manufacturing material	Technopolymer Recyclable Palazzoli
Socket Protection	With fuses
Execution	Wall mounting or on support
Outfit	WITH METAL CABINET
Insulation Class	II
Dimensions	1530X1330X690 mm
Hole type	M63
Interlocked sock.-outl. 16A 3P	2
Interlocked sock.-outl. 32A 3P	2
Interlocked sock.-outl. 63A 3P	1
Interl. sock. 16A 2P+E 230V	3
Switch type	MCB 4P - 200A
Differential protection	30mA/300mA

Reference Standards and Directives

Certification and approval marks UKCA, CE

Directives 2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/30/EU (EMC), 2014/35/EU (LVD)

Reference Standards EN 61439-1:2011, EN 61439-4:2013, EN IEC 63000:2018

The images are purely indicative. Palazzoli reserves the right to make changes without notice.