# X-CEE SOCKET COMPONENT 63A 3P+N+E 500V 7H IP66/67/68/69

**SERIES** X-CEE
**SOCKET OUTLET**
**CODE** 779347



## Datasheet

### Electrical characteristics

| | |
|---|---|
| Rated current | 63A |
| Supply Voltage | 500V 50/60Hz ● |
| Poles | 3P+N+ ⏚ |
| Clock Position | 7h |
| Rated insulation voltage | 1000 V |
| Signal plug inserted | 1 contact pilot |

### Mechanical characteristics

| | |
|---|---|
| Manufacturing material | High resistance technopolymer |
| Alveolus/plugs treatment | Nickel plated |
| Color | Grey RAL 7046, Blue RAL 5015 |
| Tightening diameter | - |
| Execution | - |
| IP Protection degree | IP66/IP67 |
| Additional IPdegree protection | IP68/IP69 - IEC 60529 |
| Shock resistance | IK10 according to IEC/EN 62262 |
| Resistance to Glow wire | 850°C (Casing), 960°C (Live contacts) |
| Flame rating according UL94 | V-0 (Live contacts), V-2 (Casing) |
| Terminals type | Screw - indirect clamping |
| Conductors section (Cu) | Min: 6 mm² ;Max: 25 mm² |
| Terminal tightening torque | 3 Nm |
| Net Weight | 0.8 KG |
| Working Environment Temp. | Min: -40°C ;Max: +60°C |
| Warehousing Temperature | Min: -50°C ;Max: +90°C |

### Reference Standards and Directives

| | |
|---|---|
| Certification and approval marks | NYCE COLOMBIA, CE, UKCA |
| Directives | 2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/35/EU (LVD) |
| Reference Standards | EN 60309-1:1999, EN 60309-1:1999/A1:2007, EN 60309-1:1999/A1AC:2014, EN 60309 -1:1999/A2:2012, EN 60309-2:1999, EN 60309-2:1999/A1:2007, EN 60309 -2:1999/A2:2012, EN IEC 63000:2018 |

The images are purely indicative. Palazzoli reserves the right to make changes without notice.

Palazzoli S.p.A. - Società unipersonale - Via F. Palazzoli, 31 - 25128 Brescia - Italy - tel. +39 030 2015.1 - fax +39 030 2015.258 - www.palazzoli.com - export@palazzoli.it