




**SERIES META
HIGH BAY**
CODE 810442DA



Model Code : META150 MT-S150-PC-40-112-DA-80-40-900-WBC-000



Datasheet

Lighting characteristics

| | |
|-------------------------------|--|
| Output flux | 21,798 lm |
| Luminous flux (TJ=25°C) | 26,100 lm |
| Luminaire power | 156 W |
| Output efficiency | 140 lm/W |
| Color temperature | 4000K |
| Optics type | Anti aging and UV resistant PMMA Lenses with efficiency >90% and transparency >95% |
| Optics | Symmetrical wide comfort 88° |
| CRI | >80 |
| Color shift | 3 MacAdam Step |
| Photobiological risk EN 62471 | RG0 - Exempt Group |
| Flicker free | < 1% |
| Life time | L90/B10 @110.000h Tq=-30°+40°C, L90 B10 @230.000h Tq=25°C |
| Emergency function | Obtainable with UPS/DALI |
| Emergency flux | - |

Electrical characteristics

| | |
|------------------------|--|
| Insulation Class | I |
| Supply Voltage | 220-240V 50/60Hz AC/DC 0/50/60Hz |
| Control system/dimming | DALI |
| Surge protection | 10kV common mode 6kV differential mode |
| Power factor | >0,95 |
| Hole type | 5 poles connector |
| Tightening diameter | Min 7 mm; Max 13 mm |
| Equipment Included | Suspension hook + connector |

Mechanical characteristics

| | |
|---------------------------|--|
| Manufacturing material | Aluminum alloy |
| Treatment type | Fluorozirconic passivation |
| Surface finishing | Atoxic, anti UV polyester paint oven polymerized |
| Colour | Grey RAL 7011 |
| Diffuser type | UV stabilized polycarbonate |
| IP Protection degree | IP66/IP67 |
| Shock resistance | IK08 according to IEC/EN 62262 |
| Corrosivity category | Equivalent to C3 (ISO 12944) |
| Mounting system | Quick hook for chain |
| Net Weight | 8.74 KG |
| Working Environment Temp. | Min: -40°C ;Max: +40°C |
| Warehousing Temperature | Min: -40°C ;Max: +70°C |
| Exposed surface | - |

Reference Standards and Directives

| | |
|----------------------------------|--|
| Warranty | 2 years extendable to 7 |
| Certification and approval marks | ENEC 05, DIN 18032-3/EN 13964 (Annex D), CE, UKCA |
| Directives | 2009/125/EC (ERP), 2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/30/EU (EMC), 2014/35/EU (LVD), Reg. EU 2019/2020 (EcoDesign) |
| Reference Standards | EN 60598-2-1:1989, EN 60598-2-22:2014, EN 60598-2-22:2014/A1:2020, EN 60598-2-22:2014/AC:2015, EN 60598-2-22:2014/AC:2016-05, EN 60598-2-22:2014/AC:2016-09, EN 60598-2-24:2013, EN 60598-2-5:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN 61547:2009, EN 62311:2008, EN 62471:2008, EN 62493:2015, EN IEC 55015:2019, EN IEC 55015:2019/A11:2020, EN IEC 60598-1:2021, EN IEC 60598-1:2021/A11:2022, EN IEC 63000:2018, IEC TR 62778:2014 |



reddot award
winner

The images are purely indicative. The indicated values of luminous flux and declared power have tolerances of +/- 7%. Palazzoli reserves the right to make changes without notice.