



**SERIES META  
ACCESSORY**  
**CODE 810991**



### Datasheet

#### Specifications

|                           |  |
|---------------------------|--|
| Net Weight                | 6.05 KG  |
| Shock resistance          | IK08 according to IEC/EN 62262                   |
| Corrosivity category      | Equivalent to C3 (ISO 12944)                     |
| Frequency                 | 50/60Hz  |
| IP Protection degree      | IP66   |
| Rated operating voltage   | 220V-240V  |
| Manufacturing material    | Aluminum alloy                                   |
| Insulation Class          | I  |
| Emergency characteristics | X 3 G 180  |
| Dimensions                | 300x280x96mm                                     |
| Treatment type            | Fluorozirconic passivation                       |
| Max conductor section     | 1.5 mm <sup>2</sup>                              |
| Colour                    | Grey RAL 7011                                    |
| Tightening diameter       | 7-13mm   |
| Min. Amb. Temp.           | 0°C  |
| Max. Amb. Temp.           | +40°C  |
| Surface finishing         | Atoxic, anti UV polyester paint oven polymerized |

#### Reference Standards and Directives

|                                  |  |
|----------------------------------|--|
| Warranty                         | 2 years extendable to 7  |
| Certification and approval marks | CE, UKCA   |
| Directives                       | 2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/30/EU (EMC), 2014/35/EU (LVD)   |
| Reference Standards              | EN 55015:2013, EN 60598-1:2015, EN 60598-1:2015/A1:2018, EN 60598-1:2015/AC:2015, EN 60598-1:2015/AC:2016, EN 60598-1:2015/AC:2017, EN 60598-2-22:2014, EN 60598-2-22:2014/A1:2020, EN 60598-2-22:2014/AC:2015, EN 60598-2-22:2014/AC:2016-05, EN 60598-2-22:2014/AC:2016-09, EN 61000-3-2:2014, EN 61000-3-3:2013, EN 61547:2009, EN 62311:2008, EN 62493:2015, EN IEC 63000:2018 |

The images are purely indicative. Palazzoli reserves the right to make changes without notice.