



**SERIES META
ACCESSORY**
CODE 810992



Datasheet

Specifications

Net Weight	5.46 KG
Shock resistance	IK08 according to IEC/EN 62262
Corrosivity category	Equivalent to C3 (ISO 12944)
Frequency	50/60Hz
IP Protection degree	IP66
Rated operating voltage	220V-240V
Manufacturing material	Aluminum alloy
Emergency characteristics	X 3 G 60
Dimensions	300x280x96mm
Hole type	M20
Treatment type	Fluorozirconic passivation
Colour	Grey RAL 7011
Tightening diameter	7-13mm
Min. Amb. Temp.	0°C
Max. Amb. Temp.	+40°C
Surface finishing	Atoxic, anti UV polyester paint oven polymerized

Reference Standards and Directives

Certification and approval marks CE, UKCA

Directives 2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/30/EU (EMC), 2014/35/EU (LVD)

Reference Standards EN 55015:2013, EN 60598-1:2015, EN 60598-1:2015/A1:2018, EN 60598-1:2015/AC:2015, EN 60598-1:2015/AC:2016, EN 60598-1:2015/AC:2017, EN 60598-2-22:2014, EN 60598-2-22:2014/A1:2020, EN 60598-2-22:2014/AC:2015, EN 60598-2-22:2014/AC:2016-05, EN 60598-2-22:2014/AC:2016-09, EN 61000-3-2:2014, EN 61000-3-3:2013, EN 61547:2009, EN 62311:2008, EN 62493:2015, EN IEC 63000:2018

The images are purely indicative. Palazzoli reserves the right to make changes without notice.