




**SERIES TIGUA
FLOODLIGHT
CODE 817108**



Model Code : TIGUA LED TL-F2-GL-40-08-00-80-40-700-AW-000



Datasheet

Lighting characteristics

| | |
|--------------------------------------|--|
| Output flux | 7,966 lm |
| Luminous flux (T _J =25°C) | 9,250 lm |
| Luminaire power | 67 W |
| Output efficiency | 118.9 lm/W |
| Color temperature | 4000K |
| Optics type | Anti aging and UV resistant PMMA Lenses with efficiency >90% and transparency >95% |
| Optics | Asymmetric wide 23° |
| CRI | >80 |
| Color shift | 4 MacAdam Step |
| Photobiological risk EN 62471 | RG0 - Exempt Group |
| UGR index | - |
| Flicker free | < 1% |
| Life time | L80/B20 @100.000h T _q = -30° +40°C |
| Emergency function | - |
| Emergency flux | - |

Electrical characteristics

| | |
|------------------------|---------------------------------------|
| Insulation Class | II |
| Supply Voltage | 220V-240V 50/60Hz |
| Control system/dimming | Standard on-off |
| Surge protection | 8kV common mode 6kV differential mode |
| Power factor | >0,95 |
| Hole type | 2 poles connector |
| Max conductor section | 1.5 mm ² |
| Tightening diameter | Min 7 mm; Max 13 mm |

Equipment Included Connector



**reddot award
winner**

Mechanical characteristics

| | |
|---------------------------|---|
| Manufacturing material | Marine aluminium alloy (EN 44300) |
| Treatment type | Fluorozirconic passivation |
| Surface finishing | Atoxic, anti UV polyester paint oven polymerized |
| Colour | Grey RAL 7011 |
| Diffuser type | Extraclear tempered glass 4 mm |
| IP Protection degree | IP66 |
| Shock resistance | IK08 according to IEC/EN 62262 |
| Corrosivity category | Equivalent to C5(M)/C4(H) (ISO 12944) |
| Mounting system | Adjustable bracket -135° +135° |
| Net Weight | 6.437 KG |
| Working Environment Temp. | Min: -30°C ;Max: +40°C |
| Warehousing Temperature | Min: -40°C ;Max: +70°C |
| Exposed surface | Lateral: 0,03 m ² - Front: 0,13 m ² |

Reference Standards and Directives

| | |
|----------------------------------|--|
| Warranty | 2 years extendable to 7 |
| Certification and approval marks | CE, ENEC 05, UKCA, DIN 18032-3/EN 13964 (Annex D) |
| Directives | 2009/125/EC (ERP), 2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/30/EU (EMC), 2014/35/EU (LVD), Reg. EU 2019/2020 (EcoDesign) |
| Reference Standards | EN 55015:2013, EN 60598-1:2015, EN 60598-1:2015/A1:2018, EN 60598-1:2015/AC:2015, EN 60598-1:2015/AC:2016, EN 60598-1:2015/AC:2017, EN 60598-2-1:1989, EN 60598-2-5:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN 61547:2009, EN 62311:2008, EN 62471:2008, EN 62493:2015, EN IEC 63000:2018, IEC TR 62778:2014 |

The images are purely indicative. The indicated values of luminous flux and declared power have tolerances of +/- 7%. Palazzoli reserves the right to make changes without notice.