TIGUA SUSPENSION 24LEDS GLASS DIFFUSER ELLIPTICAL BEAM OPTIC IP66

SERIES TIGUA
HIGH BAY
CODE 817474







Model Code : TIGUA TS1-TG-40-24-B-V10-000-80-40-0650-ELLI-000

Datasheet

Lighting characteristics

Output flux	20,627 lm
Luminous flux (TJ=25°C)	27,750 lm
Luminaire power	182 W
Output efficiency	113.3 lm/W
Color temperature	4000K
Optics type	Anti aging and UV resistant PMMA Lenses with efficiency>90% and transparency >95%
Optics	Simmetrica ellittica comfort 95°X41°
CRI	>80
Color shift	4 MacAdam Step
Photobiological risk EN 62471	RG0 - Exempt Group
UGR index	<22
Flicker free	< 1%
Life time	L80/B20 @120.000h Tq=-30°+40°C
Emergency function	-
Emergency flux	-

Mechanical characteristics

Manufacturing material	Marine aluminium alloy (EN 44300)
Treatment type	Fluorozirconic passivation
Surface finishing	Atoxic, anti UV polyester paint oven polymerized
Colour	Grey RAL 7011
Diffuser type	Extraclear tempered glass 4 mm
IP Protection degree	IP66
Shock resistance	IK08 according to IEC/EN 62262
Corrosivity category	Equivalent to C5(M)/C4(H) (ISO 12944)
Mounting system	Double chain or busbar
Net Weight	6.45 KG
Working Environment Temp.	Min: -40°C ;Max: +40°C
Warehousing Temperature	Min: -40°C ;Max: +70°C
Exposed surface	-

Electrical characteristics

Insulation Class	I
Supply Voltage	220V-240V 50/60Hz
Control system/dimming	Dimming 1-10V
Surge protection	8kV common mode 6kV differential mode
Power factor	>0,95
Hole type	5 poles connector
Max conductor section	1.5 mm^2
Tightening diameter	Min 7 mm; Max 13 mm

Equipment Included	Connector suspension hook-

Reference Standards and Directives

Warranty	2 years extendable to 7
Certification and approval marks	CE, UKCA, ENEC 05, DIN 18032-3/EN 13964 (Annex D)
Directives	2009/125/EC (ERP), 2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/30/EU (EMC), 2014/35/EU (LVD), Reg. EU 2019/2020 (EcoDesign)
Reference Standards	EN 60598-2-5:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN 61547:2009, EN 62311:2008, EN 62471:2008, EN 62493:2015, EN IEC 55015:2019, EN IEC 55015:2019/A11:2020, EN IEC 60598-1:2021, EN IEC 60598-1:2021/A11:2022, EN IEC 63000:2018, IEC TR 62778:2014

reddot award winner

The images are purely indicative. The indicated values of luminous flux and declared power have tolerances of +/- 7%. Palazzoli reserves the right to make changes without notice.

Palazzoli S.p.A. - Società unipersonale - Via F. Palazzoli, 31 - 25128 Brescia - Italy - tel. +39 030 2015.1 - fax +39 030 2015.258 - www.palazzoli.com - export@palazzoli.it