




**SERIES RINO
FIXTURE**
CODE 831191



Datasheet

Specifications

Net Weight	1.04 KG
Shock resistance	IK07 according to IEC/EN 62262
Frequency	0/50/60Hz
IP Protection degree	IP66
Rated operating voltage	230V CA-CC
Manufacturing material	Aluminum alloy
Insulation Class	I
Lamp power	MAX 75W(Ta+50°C)/50W(Ta+70°C)
Lampholder type	E27
Dimensions	226X130 mm
Hole type	M20
Diffuser type	TRANSPARENT PRISMATIC GLASS
Min. Amb. Temp.	-40°C
Max. Amb. Temp.	+70°C

Reference Standards and Directives

Certification and approval marks CB DEKRA, UKCA, CE

Directives 2009/125/EC (ERP), 2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/35/EU (LVD), Reg. EU 2019/2020 (EcoDesign)

Reference Standards EN 60598-1:2015, EN 60598-1:2015/A1:2018, EN 60598-1:2015/AC:2015, EN 60598-1:2015/AC:2016, EN 60598-1:2015/AC:2017, EN 60598-2-1:1989, EN IEC 63000:2018

Equipment Included

The images are purely indicative. The indicated values of luminous flux and declared power have tolerances of +/- 7%. Palazzoli reserves the right to make changes without notice.