



**SERIES FIT 55**  
**ROADWAY LIGHT**  
**CODE 833231MV**



Model Code : FIT 55 F55-S2-TGL-40-28-VMN-70-30-1000-ST1-LD-000

### Datasheet

#### Lighting characteristics

Output flux	11,370 lm
Luminous flux (TJ=25°C)	13,644 lm
Luminaire power	86 W
Output efficiency	132 lm/W
Color temperature	3000K
Optics type	Ultra bright aluminium 99,9% reflector

Optics	Street narrow ST
--------	------------------

CRI	CRI >= 70 (typical - tolerances according to EN62717)
-----	---

Color shift	4 MacAdam Step
-------------	----------------

Photobiological risk EN 62471	RG0 - Exempt Group
-------------------------------	--------------------

Flicker free	< 1%
--------------	------

Life time	L80 B10 @150.000H Tq=25°C
-----------	---------------------------

#### Mechanical characteristics

Manufacturing material	Aluminum alloy
Treatment type	Fluorozirconic passivation
Surface finishing	Atoxic, anti UV polyester paint oven polymerized
Colour	Grey RAL 7011
Diffuser type	Extraclear tempered glass 4 mm
IP Protection degree	IP66
Shock resistance	IK08 according to IEC/EN 62262
Corrosivity category	Equivalent to C5(M)/C4(H) (ISO 12944)
Mounting system	Fixing pole D42-76mm with adjustment -20°/+20°
Net Weight	4.5 KG
Working Environment Temp.	Min: -40°C ;Max: +40°C
Warehousing Temperature	Min: -40°C ;Max: +70°C
Exposed surface	Lateral: 0,03 m2 - Front: 0,13 m2

#### Electrical characteristics

Insulation Class	II
------------------	----

Supply Voltage	220V-240V 50/60Hz
----------------	-------------------

Control system/dimming	Midnight bilevel
------------------------	------------------

Surge protection	10kV common mode 6kV differential mode
------------------	--

Power factor	>0,95
--------------	-------

Hole type	M20
-----------	-----

Max conductor section	2.5 mm <sup>2</sup>
-----------------------	---------------------

Tightening diameter	Min 7 mm; Max 13 mm
---------------------	---------------------

Equipment Included	-
--------------------	---

#### Reference Standards and Directives

Warranty	2 years extendable to 7
Certification and approval marks	UKCA, CE, ENEC PLUS 03, ENEC 05
Directives	2009/125/EC (ERP), 2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/30/EU (EMC), 2014/35/EU (LVD), Reg. EU 2019/2020 (EcoDesign)
Reference Standards	EN 60598-2-3:2003, EN 60598-2-3:2003/A1:2011, EN 60598-2-3:2003/AC:2005, EN 61000-3-2:2014, EN 61000-3-3:2013, EN 61547:2009, EN 62311:2008, EN 62471:2008, EN 62493:2015, EN IEC 55015:2019, EN IEC 55015:2019/A11:2020, EN IEC 60598-1:2021, EN IEC 60598-1:2021/A11:2022, EN IEC 63000:2018, IEC TR 62778:2014

The images are purely indicative. The indicated values of luminous flux and declared power have tolerances of +/- 7%. Palazzoli reserves the right to make changes without notice.