






**SERIES TIGUA-EX
FLOODLIGHT**
CODE 837224EX



Model Code : TIGUA-EX F-Z2-TGL-24-DA-70-40-500-A23-PL20-000

Datasheet

Lighting characteristics

Output flux	18,000 lm
Luminous flux (TJ=25°C)	21,600 lm
Luminaire power	141 W
Output efficiency	128 lm/W
Color temperature	4000K
Optics type	UV-stabilized polycarbonate lens
Optics	Asymmetric wide 23°
CRI	CRI >= 70 (typical - tolerances according to EN62717)
Color shift	4 MacAdam Step
Photobiological risk EN 62471	RG0 - Exempt Group
UGR index	-
Flicker free	< 1%
Life time	L90/B10 @110.000h Tq=-30°+40°C, L90 B10 @230.000h Tq=25°C
Emergency function	Obtainable with UPS/DALI
Emergency flux	-

Electrical characteristics

Insulation Class	I
Supply Voltage	160-277 Vac 160-250 Vdc 0/50/60Hz
Control system/dimming	DALI
Surge protection	8kV common mode 6kV differential mode
Power factor	>0,98
Hole type	Terminal block with cable gland M20
Max conductor section	2.5 mm²
Tightening diameter	Min 7 mm; Max 13 mm

Equipment Included

Cable gland ATEX M20

Mechanical characteristics

Manufacturing material	Marine aluminium alloy (EN 44300)
Treatment type	Fluorozirconic passivation
Surface finishing	Atoxic, anti UV polyester paint oven polymerized
Colour	Black RAL 9005
Diffuser type	Extraclear tempered glass 4 mm
IP Protection degree	IP66
Shock resistance	4J (IEC 60079-0)
Corrosivity category	Equivalent to C5(M)/C4(H) (ISO 12944)
Mounting system	Adjustable bracket -135° + 135°
Net Weight	6.5 KG
Working Environment Temp.	Tmin: -40°C ; Tmax1: +40°C ; Tmax2: -
Warehousing Temperature	Tmin: -40°C ; Tmax: +70°C
Exposed surface	Lateral: 0,03 m2 - Front: 0,13 m2

Atex characteristics

ATEX application zone	Zones 2-21-22
Dust Atex execution (Tmax1)	II 2D - Ex tb IIIC T85°C Db
Gas Atex execution (Tmax1)	II 3G - Ex ec mc IIC T4 Gc
Dust Atex execution (Tmax2)	II 2D - -
Gas Atex execution (Tmax2)	II 3G - -

Reference Standards and Directives

Warranty	2 years extendable to 7
Certification and approval marks	IECEx, EX, CE
Directives	2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/30/EU (EMC), 2014/34/EU (ATEX)
Reference Standards	EN 60079-18:2015, EN 60079-18:2015/A1:2017, EN 60079-31:2014, EN 60079-7:2015, EN 60079-7:2015/A1:2018, EN 60598-2-24:2013, EN 60598-2-5:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN 61547:2009, EN IEC 55015:2019, EN IEC 55015:2019/A11:2020, EN IEC 60079-0:2018, EN IEC 60598-1:2021, EN IEC 60598-2-1:2021, EN IEC 60598-2-22:2022, EN IEC 63000:2018

The images are purely indicative. The indicated values of luminous flux and declared power have tolerances of +/- 7%. Palazzoli reserves the right to make changes without notice.