




SERIES ALARM-Ex
SIREN
CODE 900473EX



Datasheet

Specifications

Net Weight	1.23 KG
Rated current	0,14A
Frequency	50/60Hz
IP Protection degree	IP66
Poles	2P+ $\frac{1}{2}$
Rated operating voltage	230V
Manufacturing material	Aluminum alloy
power	33,4 VA
Hole type	M20
Sound level at 1 mt.	101/99dB dB
Acoustic Signal Type	D - continuous sound according to manual control
Operational working temp	-40 T 40 °C

Reference Standards and Directives

Certification and approval marks CE, NYCE COLOMBIA, EX, IECEx

Directives 2011/65/EU (RoHS), 2014/30/EU (EMC), 2014/34/EU (ATEX)

Reference Standards EN 60079-31:2014, EN 60079-7:2015/A1:2018, EN 62080:2009/A2:2015, EN 62080:2009, EN IEC 60079-0:2018, EN IEC 63000:2018

Atex characteristics

ATEX application zone	Zones 2-21-22
Dust Atex execution (Tmax1)	II 2D - Ex tb IIIC T85/T90°C Db
Gas Atex execution (Tmax1)	II 3G - Ex ec IIC T3 Gc

The images are purely indicative. Palazzoli reserves the right to make changes without notice.