




The spacer integrated with the lamp body makes the product compact. Adjustable bracket to allow movements in all directions. Made of AISI 316L stainless steel. Flush black silk-screened glass extra-clear tempered, 4 mm thick. Single emission with one LED. 21° optic at 2700K. Integrated power supply. HCT inox graphite colored surface finish.



## Datasheet

### Lighting characteristics

Output flux	408 lm
Luminous flux (TJ=25°C)	543 lm
Luminaire power	5 W
Light source type	LED
Color temperature	2700K
Optics type	PMMA
Optics	21°
CRI	CRI >= 80 (typical - tolerances according to EN62717)
Life time	L80/B10 @100.000h Ta=25°C

### Mechanical characteristics

Manufacturing material	Stainless steel AISI 316L
Dimensions	138X60X70 mm
Surface finishing	INOX GRAPHITE
Diffuser type	Extraclear tempered glass
IP Protection degree	IP66
Shock resistance	IK08 according to IEC/EN 62262
Execution	Wall mounting
Driveability	-
Working Environment Temp.	Min: -20°C ;Max: +35°C
Warehousing Temperature	Min: -30°C ;Max: +70°C

### Electrical characteristics

Insulation Class	II
Supply Voltage	230-240 Vac 50/60Hz
Control system/dimming	Standard on-off
Power Supply Unit	Integrated
Hole type	(1+1)x0,75 mmq

### Reference Standards and Directives

Warranty	2 years extendable to 5
Certification and approval marks	CE

The images are purely indicative. The indicated values of luminous flux and declared power have tolerances of +/- 7%. Palazzoli reserves the right to make changes without notice.