



AISI 316L stainless steel wall lighting fixture with flange. Diffuse lighting at 2700K. Polycarbonate lenses. Installation with bracket for surface mounting (or with plug for plasterboard, wood, and corrugated surfaces) provided as an accessory. Remote power supply. Inox Graphite HCT surface finish.



## Datasheet

### Lighting characteristics

Output flux	108 lm
Luminous flux (TJ=25°C)	269 lm
Luminaire power	3 W
Light source type	LED
Color temperature	2700K
Optics type	-
Optics	WIDE
CRI	CRI 80
Life time	L80/B10 @100.000h Ta=25°C

### Mechanical characteristics

Manufacturing material	Stainless steel AISI 316L
Dimensions	30X30X30 mm
Surface finishing	INOX GRAPHITE
Diffuser type	Glass opal
IP Protection degree	IP65
Shock resistance	IK08 according to IEC/EN 62262
Execution	WALL MOUNTED
Mounting system	Wall-mounted
Working Environment Temp.	Min: -20°C ;Max: +35°C
Warehousing Temperature	Min: -30°C ;Max: +70°C
Driveability	-

### Electrical characteristics

Insulation Class	III
LED Driving current	700 mA
Power Supply Unit	Remote
Hole type	2x0,5 mmq R-N

### Reference Standards and Directives

Warranty	2 years extendable to 5
Certification and approval marks	CB DEKRA, UKCA, CE

The images are purely indicative. The indicated values of luminous flux and declared power have tolerances of +/- 7%. Palazzoli reserves the right to make changes without notice.